SHEEP HOCK CUTTER Model 425-20



The Jarvis Model 425-20 - hydraulically powered hock cutter for sheep.

- The 425-20 is best suited for sheep hock cutting before fleece removal. It is also suitable for beef tail removal and hog hock cutting.
- Specially designed grabber mechanism holds onto hock to prevent dropping until a trigger is released.
- Compact for easy maneuverability; robust for long, trouble-free operation.
- Super fast cutting cycle combined with high cutting force means high performance for the most demanding applications.
- Designed for optimum operator comfort.
- Anti-tie down controls for operator safety.
- Constructed from corrosion resistant materials for optimum hygiene.
- Meets national and international requirements for hygiene and safety.





SHEEP HOCK CUTTER Model 425-20

Specifications		
Drive		Hydraulic
Model 425-20		
Cutting Cycle Time		1.0 sec
Cutting Force	2000 lbf	8.90 kN
Control Handle		
Air / Dual Anti-tie Down	50 psi	3.4 bar
Blade Opening	3.7 in	94 mm
Overall Length	21 in	533 mm
Weight	25 lbs	11.3 kg
Hydraulic Power Unit		
Motor Power	5.0 hp	3728 W
Operating Voltage		30 V, 3 phase, 60 Hz
	other voltages and f	requencies available
Hose Length	16 ft	4.9 m
Oil Capacity	20 gal	76 L
Oil Viscosity at 100° F / 40° C	200 SUS	46 ISO
Overall Dimensions (with heat exchanger)	•	
Overall Dissersions (without heat avalons	34 x 24 x 28 in	864 x 610 x 711 mm
Overall Dimensions (without heat exchang	er) (1 x w x n) 31.5 x 25.4 x 29.9 in	800 x 645 x 760 mm
Maight (without all)		
Weight (without oil)	250 lbs	113 kg
Equipment Selection and Accessories		Order Number
Model 425 -20		
	Standard handles	4025148
Pistol Grip and "D" handles with leg grabber		4025143
Pi	stol Grip and "D" handles	4025149
Hydraulic Power Unit without heat exchanger with control box and hoses, 460 / 230 V, 3 phase, 60 Hz		4027266
Hydraulic Power Unit without heat exchanger with control box and houses, 440 / 415 / 380 / 220 V, 50 Hz		4027216
Hydraulic Power Unit with heat exchanger with control box and hoses, 460 / 230 V, 3 phase, 60 Hz 4027307		
Balancer	, . p. 1600, 00 112	4042037
Blade		1023680
Grabber Blade		1023681



Products for the meat and poultry industry